



Quality is in our nature

PRODUCT INFORMATION

August 2016



EUROL SYNTENCE 5W-30

Fully synthetic long-life motor oil VW 504.00/507.00; MB 229.51

Eurol® Syntence 5W-30 is a fully synthetic motor oil for use in gasoline, LPG and diesel engines of passenger cars and light duty commercial vehicles, equipped with soot filters (to meet Euro-4 exhaust emission regulations). This product has been especially developed for passenger cars and light duty commercial vehicles of the VAG group (Volkswagen, Audi, Seat and Skoda) and is suitable for very long drain intervals (up to 30.000 km for gasoline and 50.000 km for diesel engines).

Eurol® Syntence 5W-30 provides an extremely quick and stable lubricant film at the cold start and maintains this film at high temperatures, while at the same time, friction is reduced to a minimum.

Eurol® Syntence 5W-30 has been developed with Eurol OPT additive technology and contains less phosphor, sulphur and phosphate. This prevents the exhaust gas system parts (soot filters and catalytic converters) from blocking and it reduces their service life.

Eurol® Syntence 5W-30 has been especially developed to meet VW specifications 504.00 and 507.00, but is also suitable for cars where formerly VW specifications like 503.00, 506.00, 506.01, 505.01, 502.00, 500.00, 501.01 and 505.00 are prescribed.

Further tests proved that the product meets the specification MB 229.51; this oil is therefore not only universally applicable for Volkswagen, but also for Mercedes.

PERFORMANCE

ACEA A3/B4 (07) , ACEA C3 (10)

VW 504.00/507.00 (approved)

MB-Approval 229.51

Porsche C30

BMW Longlife-04 (Approved)

Meets ACEA C2 requirements concerning motor protection.

Eurol® Syntence 5W-30 is suitable for all VW-engines since 2007.

This oil is not suitable for R5 and V10 engines before 2007. For these engines VW 506.01 is prescribed explicitly. Eurol Super Ultra II 0W-30 is the recommended product for this application.

TYPICAL PROPERTIES

5W-30		
Density 20C	Kg/L	0.847
Viscosity 100C	cSt	11.7
Viscosity 40C	cSt	72.0
Viscosity -30C	cP	<6600
Viscosity Index		158
Flash point COC	C	210
Pour point	C	-42

AVAILABLE VOLUMES

E100062 - 1L, E100062 - 5L, E100062 - 60L, E100062 - 210L

The contents of this document is intended to enable the reader to orient themselves on properties and potential applications of Eurol products. The information in this document can be altered at any time and without notice because of continuous product research and development. The analytical data listed in this product data sheet are typical values. Minor deviations, which may occur during the normal manufacturing process of the product, do not affect the quality of the product. Although this text has been compiled with great care, the compiler accepts no liability for damage caused by incompleteness and / or inaccuracies in the text. The reader is advised to make the final product choice in consultation with the supplier.

