Quality is in our nature

PRODUCTINFORMATION

August 2016



EUROL TURBOCAT 15W-40

Eurol® Turbocat is a synthetic engine oil recommended for petrol and diesel engines. Because of the high viscosity index, the oil assures an excellent cold start as well as an excellent lubricating film with high temperatures.

Eurol® Turbocat takes care of trouble free functioning of the engine, because of the chosen additive package. The oil helps reducing the fuel consumption as well as reducing emission levels. Because of the unique formulation a low evaporation under severe operating conditions is guaranteed.

In addition, Eurol® Turbocat gives optimum protection against wear and has strong anti -corrosion and anti-foam characteristics as well as a high resistance against oxidation. Together with the excellent detergent/dispersant properties, this oil ensures a clean and reliable engine.

PERFORMANCE

API SL/CF
ACEA A3/B3
ACEA A3/B4 (04)
VW 500.00/505.00 (10W)
VW 501.01/505.00 (15W & 20W)
MB 229.1

TYPICAL PROPERTIES

		10W-30	10W-40	15W-40	15W-50	20W-50
Density 20C	Kg/L	0.863	0.860	0.867	0.873	0.874
Viscosity 100C	cSt	11.7	14.8	14.5	18.1	17.7
Viscosity 40C	cSt	76.5	99.1	106	140	146
Viscosity -15C	cP	-	-	-	-	<9500
Viscosity -20C	cP	-	-	<7000	<7000	-
Viscosity -25C	cP	<7000	<7000	-	-	-
Viscosity Index		147	156	141	144	134
Flash point COC	C	>190	>200	>200	>210	>210
Pour point	C	<-36	<-36	<-33	<-33	<-30
Sulphated ash	Wt%	1.0	1.0	1.0	1.0	1.0

AVAILABLE VOLUMES

E100022 - **1L**, E100022 - **4L**, E100022 - **5L**, E100022 - **60L**, E100022 - **210L**

The contents of this document is intended to enable the reader to orient themselves on properties and potential applications of Eurol products. The information in this document can be altered at any time and without notice because of continuous product research and development. The analytical data listed in this product data sheet are typical values. Minor deviations, which may occur during the normal manufacturing process of the product, do not affect the quality of the product. Although this text has been compiled with great care, the compiler accepts no liability for damage caused by incompleteness and / or inaccuracies in the text. The reader is advised to make the final product choise in consultation with the supplier.