Quality is in our nature

PRODUCTINFORMATION

August 2016



EUROL FULTRASYN 75W-90 GL3/4/5

Fully synthetic gear oil for manual gearboxes and final drives

Eurol® Fultrasyn 75W-90 is a fully synthetic, universal transmission/gear oil which can be used in both manual gearboxes as well as in final drives and where an API GL 3, 4 or 5 specification is required. By this, the oil offers excellent possibilities for reducing stock.

Eurol® Fultrasyn 75W-90 is a fully synthetic oil and can be used in the complete drive line. The special additives in this product reduce fuel consumption and eliminate shifting problems.

Eurol® Fultrasyn 75W-90 is fully compatible with synchromesh gearboxes and ensures easy shifting, even at very low temperatures.

Because of this unique formulation not only wear, but also corrosion and foam building are reduced to a minimum. At high temperatures, the oil is protected against thermal oxidation.

Eurol® Fultrasyn 75W-90 shows excellent EP (Extreme Pressure) characteristics to cope with high loads and vibrations. Viscosity drop caused by high loads is minimal, so that the right viscosity is guaranteed, even at prolonged drain intervals.

PERFORMANCE

API GL 3/4/5, MT-1
MIL-L2105 B/C/D
MIL-PRF-2105E
ZF TE-ML 01, 02B, 05B, 07A, 08A, 12, 16F, 17B, 19C
MAN 3343 S/SL
Volvo 97312
VW G 052 190
Scania STO 1:0 box
DAF
MB 235.8, 235.11
SAE J2360

TYPICAL PROPERTIES

		75W-90
Density 20C	Kg/L	0.870
Viscosity 100C	cSt	16.4
Viscosity 40C	cSt	95.8
Viscosity -40C	cP	<90000
Viscosity Index		185
Flash point COC	C	200
Pour point	C	-51

AVAILABLE VOLUMES

E110076 - **1L**, E110076 - **5L**, E110076 - **60L**, E110076 - **210L**

The contents of this document is intended to enable the reader to orient themselves on properties and potential applications of Eurol products. The information in this document can be altered at any time and without notice because of continuous product research and development. The analytical data listed in this product data sheet are typical values. Minor deviations, which may occur during the normal manufacturing process of the product, do not affect the quality of the product. Although this text has been compiled with great care, the compiler accepts no liability for damage caused by incompleteness and / or inaccuracies in the text. The reader is advised to make the final product choise in consultation with the supplier.