Quality is in our nature

PRODUCTINFORMATION

August 2016



EUROL LITHIUM GREASE MPQ-3

Universal lithium grease for various applications

Eurol® Lithium Grease MPQ (Multi Purpose Quality) is a high-quality stable grease, based on mineral oil and lithium soap as thickener. Due to the presence of additives and the strong adhesion to metals this grease has good anti-oxidant and corrosion preventing properties.

Eurol® Lithium Grease MPQ can be used up to 120°C, with peak temperatures up to 130°C. Furthermore, Eurol® Lithium Grease MPQ is suitable for high working loads, shock loads and where water and dirt may penetrate the greasing point.

Eurol® Lithium Grease MPQ guarantees optimal protection, also under heavy working conditions, extending equipment life-time and reducing maintenance costs.

PERFORMANCE

DIN K 2 K -30 (NLGI 2)
DIN K 3 K -30 (NLGI 3)
Application:
- Ball Bearings
- Wheel Hub
- Universal Joints
- Chassis Pivots

TYPICAL PROPERTIES

		NLGI 2	NLGI 3
Thickener		Lithium	Lithium
NLGI-class		2	3
Worked penetration 25C	mm/10	280	235
Dropping point	C	>180	>180
Viscosity base oil 40C	cSt	90-120	80
Temperature range	C	-30 tot +120	-30 tot +120
Four ball welding load	Kg	200	200

AVAILABLE VOLUMES

E901038 - **400G**, E901038 - **15KG**, E901038 - **50KG**, E901038 - **180KG**

The contents of this document is intended to enable the reader to orient themselves on properties and potential applications of Eurol products. The information in this document can be altered at any time and without notice because of continuous product research and development. The analytical data listed in this product data sheet are typical values. Minor deviations, which may occur during the normal manufacturing process of the product, do not affect the quality of the product. Although this text has been compiled with great care, the compiler accepts no liability for damage caused by incompleteness and / or inaccuracies in the text. The reader is advised to make the final product choise in consultation with the supplier.