# LIFTING TECHNOLOGY
# AXLE JACK

**AL II 2.0**
VP 985043




## AL II 2.0
VP 985043

The axle jack has proved successful thanks to its robust, tried and tested technology and is suitable for a load capacity of up to 2.0 t. Operation is either via manual hydraulic or hydro-pneumatic system. The axle jack can be supplemented by a wide range of accessories.

### PRODUCT DETAILS/ACCESSORIES

Powder coating in RAL 7016, anthracite
incl. carriage

incl. 2 rubber pads for lifting brackets
incl. 3 lift extenders measuring 10 / 45 / 85 mm

### TECHNICAL DATA

| | |
|---|---|
| Load capacity | 2000 kg |
| Stroke (effective stroke) | 250 mm |
| Extension length | 780 - 1610 mm |
| Max. protrusion above runway | 70 mm |

### ACCESSORIES

| | |
|---|---|
| VZ 975587 | Support Extension 130 mm (2 pcs.) |
| VZ 975597 | Plug-In Type Hard Rubber Chocks h = 50 mm |
| VZ 975598 | Lifting saddle height adjust. for vehicle center support with Axle Lift AL II |
| VZ 975711 | Support for 3-Wheelers and Trailer Stabiliser Wheels |
| VZ 975894 | Extender set Transporter for Axle lifts 2.0 t / 2.6 t |
| VZ 975821 | Axle lift carriage for pit profiles with cylindrical rollers |
| VZ 975822 | Axle lift guide rollers for pit profiles with tapered rollers |
| VZ 975644 | Support disc height-adjustable 60 mm (2 pcs) |
| VZ 975645 | Support Extension 60 mm (2 pcs.) (only in conj. with VZ 975644) |
| VZ 975646 | Rubber Support, Round (2 pcs) (only in conj. w. VZ 975644) |

**SUPPLEMENTARY CHARGES**

| | |
|---|---|
| VT 998217 | Internal transport -SOUTHAxle lift, incl. packaging |
| VT 998218 | Internal transport -NORTHAxle lift, incl. Packaging |
| VM 996144 | Montage Achslift |

MAHA SE & Co. KG / Hoyen 20 / 87490 Haldenwang / Germany
Phone: +49 8374 585 0 / Fax: +49 8374 585 0 / sales@maha.de / www.maha.de