LIFTING TECHNOLOGY
AXLE JACK

AL II 2.6 PH S
VP 985063



AL II 2.6 PH S
VP 985063

The axle jack has proved successful thanks to its robust, tried and tested technology and is suitable for a load capacity of up to 2.6 t. Operation is either via manual hydraulic or hydro-pneumatic system. The axle jack can be supplemented by a wide range of accessories.

PRODUCT DETAILS/ACCESSORIES

Narrow axle jack with large cross-beam extension
Powder coating in RAL 7016, anthracite
incl. carriage
incl. air supply set (spiral hose, guide rope)
incl. 2 rubber pads for lifting brackets
incl. 3 lift extenders measuring 10 / 45 / 85mm

TECHNICAL DATA

Load capacity	2600 kg at 8.5 bar
Min. / max. operating pressure	8.5 bar / 12 bar
Minimum air quantity	500 l/min
Stroke (effective stroke)	250 mm
Extension length	780 - 1610 mm
Max. protrusion above runway	70 mm

ACCESSORIES

VZ 975587	Support Extension 130 mm (2 pcs.)
VZ 975597	Plug-In Type Hard Rubber Chocks h = 50 mm
VZ 975598	Lifting saddle height adjust. for vehicle center support with Axle Lift AL II
VZ 975711	Support for 3-Wheelers and Trailer Stabiliser Wheels
VZ 975894	Extender set Transporter for Axle lifts 2.0 t / 2.6 t
VZ 975821	Axle lift carriage for pit profiles with cylindrical rollers
VZ 975822	Axle lift guide rollers for pit profiles with tapered rollers
VZ 975644	Support disc height-adjustable 60 mm (2 pcs)
VZ 975645	Support Extension 60 mm (2 pcs.) (only in conj. with VZ 975644)
VZ 975646	Rubber Support, Round (2 pcs) (only in conj. w. VZ 975644)

SUPPLEMENTARY CHARGES

VT 998217	Internal transport -SOUTHAxle lift, incl. packaging
VT 998218	Internal transport -NORTHAxle lift, incl. Packaging
VM 996144	Montage Achslift

MAHA SE & Co. KG / Hoyen 20 / 87490 Haldenwang / Germany
Phone: +49 8374 585 0 / Fax: +49 8374 585 0 / sales@maha.de / www.maha.de