LIFTING TECHNOLOGY
AXLE JACK

AL II 4.0 PH W
VP 985065

AL II 4.0 PH W
VP 985065

The axle jack has proved successful thanks to its robust, tried and tested technology and is suitable for a load capacity of up to 4.0 t. Operation is either via manual hydraulic or hydro-pneumatic system. The axle jack can be supplemented by a wide range of accessories.

PRODUCT DETAILS/ACCESSORIES

Powder coating in RAL 7016, anthracite
incl. carriage
incl. air supply set (spiral hose, guide rope)
incl. 2 120 mm rubber discs
incl. 2 adapter sockets for rubber discs
incl. 3 lift extenders measuring 50 / 100 / 200 mm

TECHNICAL DATA

Load capacity	4000 kg at 8.5 bar
Min. / max. operating pressure	8.5 bar / 12 bar
Minimum air quantity	500 l/min
Stroke (effective stroke)	250 mm
Extension length	796 - 1650 mm

ACCESSORIES

VZ 975821	Axle lift carriage for pit profiles with cylindrical rollers
VZ 975822	Axle lift guide rollers for pit profiles with tapered rollers

SUPPLEMENTARY CHARGES

VT 998217	Internal transport -SOUTHAxle lift, incl. packaging
VT 998218	Internal transport -NORTHAxle lift, incl. Packaging
VM 996144	Montage Achslift

MAHA SE & Co. KG / Hoyen 20 / 87490 Haldenwang / Germany
Phone: +49 8374 585 0 / Fax: +49 8374 585 0 / sales@maha.de / www.maha.de